

550,769

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
14 October 2004 (14.10.2004)

PCT

(10) International Publication Number  
**WO 2004/087329 A1**

(51) International Patent Classification<sup>7</sup>: **B05B 1/04**,  
F25C 3/04

(21) International Application Number:  
PCT/AU2004/000433

(22) International Filing Date: 2 March 2004 (02.03.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
2003901631 3 April 2003 (03.04.2003) AU

(71) Applicant and

(72) Inventor: **DODSON, Mitchell, Joe** [US/AU]; Lot 4, Simmonds Creek Road, Tawonga South, VIC 3698 (AU).

(74) Agent: **GRIFFITH HACK**; 509 St Kilda Road, Melbourne, VIC 3004 (AU).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: NOZZLES



(57) Abstract: A nozzle (10) for producing a flat spray pattern, the nozzle comprising a fluid passageway terminating in an end wall having an outlet aperture (20), the fluid passageway having at least one deflector (3, 4) that deflects the fluid towards the aperture; and adjustable means (21, 22) to vary the cross-section of the aperture, and Snowmaking equipment comprising at least one nozzle of the above kind, the nozzle being inclined upwardly to, in use, project a plume of water droplets, the nozzle being positioned adjacent a jet of compressed air, the variation in the cross-section of the aperture reflecting the characteristics of the plume.

WO 2004/087329 A1